(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 29 December 2005 (29.12.2005)

PCT

(10) International Publication Number WO 2005/123146 A1

(51) International Patent Classification⁷: C02F 1/32

A61L 2/10,

(21) International Application Number:

PCT/IT2004/000346

(22) International Filing Date:

15 June 2004 (15.06.2004)

(25) Filing Language:

Italian

(26) Publication Language:

English

- (71) Applicant (for all designated States except US): S.I.D.E.A. ITALIA S.R.L. [IT/IT]; Via di Serravalle, 1/3/5, I-50060 Molino del Piano, Pontasieve (IT).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): TAVANTI, Giacomino [IT/IT]; Via del Ninfale, 1, I-50100 Firenze (IT).
- (74) Agents: BARDINI, Marco, Luigi et al.; Società Italiana Brevetti S.p.a., Corso dei Tintori, 25, I-50122 Firenze (IT).
- (81) Designated States (unless otherwise indicated for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: IMPROVED APPARATUS FOR THE COLD STERILIZATION OF A FLUID BY ULTRAVIOLET RAYS



(57) Abstract: An apparatus for the continuous cold sterilization of a fluid (4) comprising at least one ultraviolet radiation source (2) and at least one duct (3) permeable to such radiation in which the fluid flows. The duct has a portion with helical shape (3a) around the ultraviolet radiation source (2) which is arranged in a chamber (1a) with walls having reflective surfaces. The distance between the walls and the helical portion is sufficient to allow an adequate circulation of air between them, whereby an excessive heating of the fluid is avoided. Moreover, at least the helical portion of the duct has an elliptical-shaped passage section (5) with

123146 A1